

Standalone Breathalyzer

www.hwsensor.com



AT319V Coin operated Alcohol Tester

AT319V, coin operated Breath Alcohol Tester with 7" display, is designed to measure alcohol concentration in the human body. With advanced fuel cell alcohol sensor, this device has excellent sensitivity and reproducibility. Reasonable and easy testing process, complete function makes it versatile in many occasions.

FEATURES

- Fuel cell sensor-accuracy and reliance
- Pre-calibrated sensor module-easy for maintenance
- AC110V/220V power supply
- Switchable result units(mg/l, g/l, %BAC, ‰BAC)
- Suitable for bar, restaurant, hotel, and night clubs, etc.
- Coin payment only
- 7" display to show photos, videos, advertisements, etc.

APPLICATION

Bar, hotel, restaurant, factory, workshop, office, hotel, mine, etc.

PHOTO FRAME FEATURE SETUP




Many of the picture frame functions can be adjusted to your preference. By using the SETUP option from the main menu, the following changes can be made: use the ENTER button and UP/DOWN arrows to change the options.

Function	Description	Video mode	Original. Maximum etc
Languages	Support English, Chinese etc	Display	Contrast, brightness, color, tonality etc
Boot mode	Auto play, music, video, image, calendar etc	Set time/date	Year, month, day, hour, minute, second
Slide mode	Single window, split window, three windows	Set time format	12-hour clock or 24-hour clock
Slide speed	3 sec, 5 sec, 15 sec, 30 sec 1 hour	Alarm	The state and mode of alarm clock
Photo effect	Colorful, black, dark brown	Auto power off	Optional
Slide effect	Random shutter, brick etc	Format built-in memory	Optional
Photo mode	Original ,optimization, full-screen	Reset setting	Optional
Music play mode	Re-play one, repeat, re-play all etc	Exit	Return to main screen

PHOTO FRAME MAIN FEATURES

- Create an automatic slide show with multiple transition effects and optional background music.
- Support JPEG format images and play mp3 music with the integrated stereo speakers.
- Play mpeg1, mpeg2 and mpeg4 movie files stored on supported memory cards.
- compatible with many memory cards including, SD, MMC, MS cards, Compact
- Flash as well as USB flash drives.
- Includes a credit card-sized remote control.



SPECIFICATIONS

Sensor Type	Fuel cell	Display	Four-digit digital tube
Detection Range	0.00 - 0.40%BAC, 0.00-4.00‰BAC 0.00 - 2.00mg/L; 0.00 - 4.00g/L	Power	AC110V-AC220V 50/60HZ
Accuracy	± 0.005 at 0.05%BAC	Working Environment	0°C - 50°C, ≤95% RH, No dews
Pre-set Level	0.05%BAC; 0.50‰BAC; 0.25mg/L; 0.50g/L	Working Time	Continuous
Warm-up Time	<10 seconds	Dimensions	310mm*141mm*450mm @4500g
Testing Time	< 5 Sec	Installation	Wall-mounted
		Payment term	Coins

Welcome to Hanwei !