

# **Multi Gas Detector**

# www.hwsensor.com



### **BX616 Portable Multi-gas Detector**

#### **FEATURES**


- Small size and light-weight
- · Simple operation with only 1 button
- Adjustable alarm levels and span calibration value
- STEL and TWA alarm for toxic gases
- Self protection for combustible gas sensor against high concentration
- · Battery low voltage alert
- Confidence beep
- Self-test after power on
- · Self-diagonstic and self-correction function

#### **APPLICATION**

Steelworks, petrochemical plant, oil industry, shipbuilding yard, sewage treatment plant, mine, power supply works, confined spaces etc.

BX616 is a multi-gas detector which can detect the combustible gases, O2, CO and H2S gases in the air. Its functional and watertight design (IP 66) incorporates a Bump proof, rubberized housing to meet the toughest requirement of harsh environment like underground tunnels, mines etc.

### **APPEARANCE**



- 1. Alarm indicator
- 2. Button
- 3. Sensor channel
- 4. Display screen
- 5. Buzzer
- 6. Calibration cap fasten hole
- 7. Hand strap
- 8. alligator clip
- 9. Label
- 10. charging/ communication port

#### **SPECIFICATIONS**

Measuring gas	O2	СО	H2S	Combustible	Working temperature	Toxic gases: -20°C ~ 50°C Combustible: -40°C ~ 70°C
Measuring range	0-25%VOL	0-500ppm	0-100ppm	0-100%LEL		
Sensor type	Electrochemical Catalytic				WorkinAg humidity	<95%RH (no condensation)
Measuring type	Diffuse naturally				Housing	Rubber enclosure
Response time	T <sub>90</sub> <30s				Standard accessories	Operation manual, calibration cap, charger, screwdriver, USB cable
Display	LCD screen					
Audible	≥80dB at 1m				Dimension & weight	120mm*68mm*30mm, about 220g
Alarm method	Visual, audible and vibrative signals				Ingress protection	IP66
Battery	DC3.7V 1800mAh Lithium battery					<b>—</b> #00 F : #0 T4 0
Operating life	≥8h per charge (Charging time: 4-6h)				Ex grade	II 2G Ex ia IIC T4 Ga or
Event log	2000 events					II 2G EX dD la liC 14 GD

## Welcome to Hanwei!



# 汉威科技集团股份有限公司 Hanwei Electronics Group Corporation

ADD: No.169 Xuesong Road, National & High Tech Zone, Zhengzhou 450001, Henan, China P.C: 450001

www.hwsensor.com

TEL: 86-371-67169070 / 80 FAX: 86-371-67169090

E-mail: sales@hwsensor.com