



Natural or LPG Gas Alarm



GK

FEATURES

- Best selling model
- Reliable performance
- Optional valve and relay output

APPLICATION

The GK gas alarm is welcomed by customers due to its good design and stable performance. It can test different gases and response rapidly.

SPECIFICATIONS:

Measuring gas	Natural gas or LPG	Working Environment	Temperature: -10°C ~ 50°C
Working voltage	AC220V±15%/AC110V±15% 50Hz~60Hz		Humidity: <95%RH
Sensor life	>3 years	Alarm sound	≥85dB(1m)
Alarming level	10%LEL	Optional function	<input type="checkbox"/> gas shut off valve <input type="checkbox"/> relay output

Gas alarm with UPS battery--GK

FEATURES

- With extra UPS battery
- Continuously work for 10 hours without electricity
- Optional valve and relay output

APPLICATION

The GK with UPS battery is used to test natural gas or LPG in home. It's specially design for countries which have limit for using electricity.



SPECIFICATIONS

Measuring gas	Natural gas or LPG	Battery volume	10400mAh
Working voltage	DC12V	Alarming level	10%LEL

Combined CH4&CO alarm--GK

FEATURES

- Available to test both CH4 and CO
- Best selling model
- Optional valve and relay output

APPLICATION

The GK combined alarm is used to test both natural gas and carbon monoxide in home. It's a two in one detector so it shall save more home space with much economic price.

SPECIFICATIONS

Measuring gas	Natural gas and carbon monoxide	Alarming level	CH4: 10%LEL;
Working voltage	AC220V±15%/AC110V±15% 50Hz~60Hz DC12V		CO: Follow EN50291

Welcome to Hanwei !



汉威科技集团股份有限公司
Hanwei Electronics Group Corporation

ADD: No.169 Xuesong Road,National&HighTech Zone,
Zhengzhou 450001, Henan, China P.C: 450001

www.hwsensor.com
TEL: 86-371-67169070 / 80
FAX: 86-371-67169090
E-mail: sales@hwsensor.com